



- **BONDING KEY COATS**
- **CEMENT RENDERS/PLASTERS**
- **COLOURED RENDERS**
- **GYPSUM PLASTERS**
- **MASONRY MORTARS**
- ▶ FLOOR SCREEDS
- **CONCRETE REPAIR MORTARS**
- NON SHRINK GROUTS













www.rakfix.com

MACHINE PLASTER FROM RAS AL KHAIMAH

RAK fix is a leading manufacturer of dry mix mortar based on cement, lime and gypsum. RAK fix is located in Ras Al Khaimah, which is well known for its high quality natural mineral resources.



RAK fix PLANT

RAK fix dry mix mortars are transported in dry form to the construction site, where only water is added to the dry mortar in specified quantity just before the application.

RAK fine has a wide range of machines to suit all applications and volume of work. For a large scale of plaster job, plastering machines with the silo system is the perfect solution. Plastering machines mix and spray the wet mortar on to the wall or ceiling where it is leveled and finished by skilled masons. RAK five provides PFT G4 plastering machines to get a consistent quality of wet plaster mortar. An uninterrupted supply of dry mix plaster from the silo, which stands at a convenient place, ensures a continuous work and high output. For high-rise towers relay stations are provided to convey the dry mortar to any desired height. For masonry mortar and screed RAK five provides horizontal screw mixer for continuous supply of wet mortar.

RAK fix offers jobsite training for the masons for machine operation and application of dry mix products.

RAK fix dry mix mortars are designed in accordance with the relevant standard specifications of BS, ASTM and DIN. The product range includes different kind of plasters/renders, coloured decorative renders, ordinary and special masonry mortars, screeds, concrete repair mortar and grouts.

Advantages of the RAK fix dry mix mortars

- Saving in time and labour.
- ▶ Consistent quality
- ▶ Reduction in overhead cost
- ▶ Wider choice of material and application process
- Speed of application with machine
- ▶ Pollution and hazards free mechanized process of application
- Accurate account of material used.
- ▶ Early removal of scaffolding

RAK fix offers the following 2 type of delivery systems

- ▶ Paper bags in 25-50 kg, palletized and shrink wrapped
- ▶ Silo in 12-20m³, with option of refilling at site by tankers



CONTEMPORARY GARDEN



PLASTER APPLICATION



QUALITY CONTROL LAB

An experienced Sales and Technical Support Service Team of RAK fix is available to offer you the right kind of material and services to the highest satisfaction.

	Bondcrete		R	AK fix	010		
Bonding Keycoat - Cement based	^{50kg} Bags	Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description		
		Bonding key coat for normal concrete surface Provides rough textured surface for plastering	430m ² @ 2mm thickness	40 bags	Dry mix bonding compound consisting of OPC, quality enhancing additives and processed mineral aggregates. Applied on concrete surface to achieve mechanical key for plastering.		
	Bondcrete		RAK fix 012				
	-01	Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description		
	50kg Bags	Bonding key coat for densified concrete surface Provides rough textured surface for plastering	430m ² @ 2mm thickness	40 bags	Dry mix bonding compound consisting of OPC, quality enhancing additives and processed mineral aggregates. Applied on densified smooth concrete surface to achieve mechanical key for plastering.		
Bonc	Bondcrete		RAK fix 014				
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description		
	50kg Bags	Bonding key coat for ultra smooth and impermeable concrete surface. Provides rough textured surface for plastering	430m² @ 2mm thickness	40 bags	Dry mix bonding compound consisting of OPC, quality enhancing additives and processed mineral aggregates. Applied on densified ultra smooth and impermeable concrete surface to achieve mechanical key for plastering.		
	Cement lime plaster RAK fix 020						
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description		
int Based	Silo Bags	Suitable for plastering/ rendering of normal concrete blocks and concrete background. Easy to apply by machine and by hand Excellent workability Thickness 10-25 mm in single coat	42m² @ 15mm thickness	40 bags	Dry mix mortar consisting of OPC, hydrated lime, quality enhancing additives and processed mineral aggregates. Applied with machine on concrete blocks and concrete background on interiors and exteriors.		
Cement	Cement lime plaster for AAC/Concrete blocks RAK fix 022						
ers -		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description		
Renders/Plasters -	50kg Silo Bags	Suitable for all types of masonry backgrounds Strength compatible with AAC blocks Thickness 15-25mm in two coats	42m² @ 15mm thickness	40 bags	Dry mix mortar consisting of OPC, hydrated lime, quality enhancing additives and processed mineral aggregates. Applied with machine on AAC lightweight blocks on interiors and exteriors.		
Re	Light weight cement lime plaster RAK fix 024						
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description		
	30kg Silo Bags	Light weight plaster More yield and coverage 10-25 mm thick in single coat Suitable for all masonry and concrete surfaces	50m ² @ 15mm thickness	40 bags	Dry mix mortar consisting of OPC, hydrated lime, quality enhancing additives, EPS beads and processed mineral aggregates . Applied with machine on interiors and exteriors.		
	Cement pla	ster	R	AK fix	025		
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description		
	Silo Bags	 High strength - 10N/mm² Minimum 20mm thick render Hand / machine applied 	30m ² @ 20mm thickness	40 bags	Dry mix mortar consisting of OPC, quality enhancing additives and processed mineral aggregates . Applied on exteriors plinth of the building.		

	High s	trengt	th plaster	R	AK fix	026
	Silo	50kg Bags	Benefits • High strength ≥15N/mm² • 15 - 50 mm thickness • Suitable for artificial rock work and landscaping	Approx. Coverage [per ton] 38 m² @ 15mm thickness	Bags per pallet 40 bags	Product Description Dry mix mortar consisting of OPC, hydrated lime, quality enhancing additives, fibres and processed mineral aggregates. Applied with machine or by hand.
	Smoot	hing _l	plaster	R	AK fix	028
	Silo	50kg Bags	 Finishing coat plaster 3 - 5 mm thickness Suitable for ceiling 	Approx. Coverage [per ton] 162 m² @ 4mm thickness	Bags per pallet 40 bags	Product Description Dry mix fine mortar consisting of OPC, hydrated lime, quality enhancing additives and processed mineral aggregates. Applied with machine or by hand
	Pigmented cement render RAK fix 030					
Coloured Kenders	Silo	50kg Bags	Variety of light shades Landscape and heritage finish Suitable for masonry and concrete surfaces 15 - 25 mm double coat render	Approx. Coverage [per ton] 42m² @ 15 mm thickness	Bags per pallet 40 bags	Product Description Premixed pigmented render consisting of white Portland cement, inorganic pigments, quality enhancing additives and processed marble aggregates . Applied with machine on masonry and concrete background.
	Texture	ed Rei	nder	R	AK fix	032
	RAK fize	50kg Bags	Variety of light shades Variety of textures Suitable for masonry and concrete surfaces 15 - 25 mm double coat render	Approx. Coverage [per ton] 35m² @ 15mm thickness	Bags per pallet 40 bags	Product Description Premixed pigmented textured render consisting of white Portland cement, inorganic pigments, quality enhancing additives and processed marble aggregates. Applied with machine on masonry and concrete background.
	Rock p	laster	1	R	AK fix	034
	Silo	50kg Bags	Benefits • High strength >15N/mm² • Landscape and heritage finish • Variety of light shades • 15 - 50 mm thickness	Approx. Coverage [per ton] 38 m² @ 15 mm thickness	Bags per pallet 40 bags	Product Description Premixed pigmented mortar consisting of white Portland cement, quality enhancing additives, fibres and processed mineral aggregates. Applied with machine or by hand to achieve hard rock like features.
	Gypsum plaster - Standard RAK fix 040					
iters	RAKSiz	25kg	Plaster for internal walls and ceilings One coat application in 12-25 mm No water curing Provides coaling effect.	Approx. Coverage [per ton] 58m² @ 12mm thickness	Bags per pallet 60 bags	Product Description Premixed dry mortar consisting of hemi-hydrated gypsum, hydrated lime, quality enhancing additives and processed mineral aggregates. Applied with machine on interior walls and callings.

RAK fix 042 Gypsum plaster - Thin coat Bags per pallet Approx. Coverage [per ton] **Product Description** Benefits 208 m² @ 4mm thickness • Thin coat finishing plaster, 3-5mm 60 bags Premixed dry mortar consisting of hemi-hydrated gypsum, 25kg hydrated lime, quality enhancing additives and processed • Applied on concrete and plaster surface mineral aggregates. Applied with machine or by hand on • No water curing plastered walls and ceilings. • Machine/hand applied Bags

• Provides cooling effect

Silo

Bags

ceilings.

	Masonry mo	ortar for concrete blocks	RAKfix		050	
Masonry Mortars		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description	
	50kg Silo Bags	 Masonry mortar for laying/fixing concrete blocks Excellent workability Dry and wet pumpable 	Yield 560 ltr/ton	40 bags	Premixed masonry mortar consisting of OPC, hydrated lime quality enhancing additives and processed mineral aggregates Applied with trowel to fix normal concrete blocks.	
	Masonry mo	ortar for AAC blocks	RAK fix		052	
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description	
	Silo Bags	Adhesive mortar for fixing AAC light weight blocks Thin bed mortar 3-5 mm thick. Excellent adhesion on smooth and porous AAC blocks	Yield 615 ltr/ton	40 bags	Premixed thin bed adhesive mortar consisting of OPC, hydrate lime, quality enhancing additives and processed minera aggregates . Applied with combing trowel to fix AAC blocks.	
	Floor screed		RAK fix		060	
Floor screed		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description	
	50kg Silo Bags	 Suitable for 20-100 mm thickness Self compacting Excellent workability 15-40 N/mm² strength 	25m² @20 mm thickness	40 bags	Dry mix screed for rough and uneven concrete floors. Consists o OPC, quality enhancing additives and mineral aggregates.	
	Repair mort	R	AK fix	070		
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description	
air Mortars	50kg Bags	For concrete and masonry repairs Strength 20N/mm² Shrinkage compensated mortar	Yield 620 ltr/ton	40 bags	Dry mix mortar for concrete and masonry repairs. Consists of OPC, hydrated lime, special quality enhancing additives and mineral aggregates. Suitable for up to 10 mm thick repair.	
re Ke	Repair mortar- high strength RAK fix 072					
Concrete Rep		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description	
	50kg Bags	• For concrete and masonry repairs • Shrinkage compensated mortar • Strength 40N/mm²	Yield 530 ltr/ton	40 bags	Dry mix mortar for concrete repairs. Consists of OPC, hydrater lime, quality enhancing additives and mineral aggregates Applied up to 20 mm in each layer.	
	Non shrink grout- moderate strength RAK fix 080					
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description	
Non shrink grouts	50kg Silo Bags	 Strength 40N/mm² Shrinkage compensated mortar Suitable for pouring 	Yield 510 litre/ton	40 bags	Non shrink anchoring dry mix mortar for fixing machine foundation and other similar type of application. Consists o OPC, quality enhancing additives and mineral aggregates.	
	Non shrink grout- high strength		RAK fix		082	
		Benefits	Approx. Coverage [per ton]	Bags per pallet	Product Description	
	RAK /i.e 50kg	 Strength 70N/mm² Shrinkage compensated mortar Suitable for pouring 	Yield 510 litre/ton	40 bags	Non shrink anchoring dry mix mortar for fixing machine foundation and other similar type of application. Consists o OPC, quality enhancing additives and mineral aggregates.	

BENEFITS OF SILO SYSTEM


- Saving in time and man power
- Saving in number of manual operations
- No handling and storage of bags at the construction site
- Availability of product in required quantity
- Full protection of material from theft, weather condition & spillage
- Needs less space
- Highly efficient mechanised process of plastering







P.O.Box: 6575, Ras Al Khaimah, U.A.E Tel: (+971) 07 24 47 260, Fax: (+971) 07 24 47 261, E-mail: rakfix@rakfix.com, Website: www.rakfix.com



Up to 90 meter, higher applications are possible when "Relay Stations" are installed

