



STYLE NO: EOK

TECH SCORE - FLEX S3 (70720)

EN EN ISO 20345:2011 SRC

EN 61340-4-3 / DGUV 112-191

MADE IN FRANCE

Materials

- Upper > Full Nubuck Leather
- Lining > ARTICO®
- Toe Cap > Composite LIGHT SYSTEM®
- Midsole > Composite FLEX SYSTEM®
- Insole > Thermoformed in active carbon dual density foam
- Outsole > PU 2D, TECH SOLE®

Features

- > Water-resistant full nubuck leather upper
- > Anti-magnetic and thermal insulated composite midsole
- > Ultralight and extra wide 200 joules composite toe cap
- > Anti-static, ESD (electro-static discharge) and antibacterial FRESH TECH® insole
- > TECH SOLE® ankle anti-twist system, antistatic, HI-CI (Heat Insulated/Cold Insulated) outsole
- > Slip-resistance sole / oil resistant FO (fuel oil)
- > ARTICO® black color lining up to the toes gives the slipper feeling
- > Bellows tongue in leather, lining ARTICO® and padded with 10mm thick foam
- > Ankle protection - ON STEAM® microfibre black color, lining ARTICO® and padded with 10 mm thick foam
- > Ideal for outside work
- > Available in size 38 to 46
- > 1 year warranty

Recommended Industries/Use

- > Automotive and Part Manufacturer
- > Building and Construction
- > Logistics
- > Maintenance Services
- > Transportation
- > High - Tech

PACKAGING

10 pairs per carton

STYLE NO: PRS

VESTA

PART NO: 15113

EN ISO 20345:2011 S2 SRC

MADE IN FRANCE



Materials

Upper: Dry Tek Material, thickness 2.2mm, acid resistant, washable and breathable

Lining: Cambrelle Amicor+, with refreshing microcells perfume system

Tongue: Dry Tek Material

Toe Cap: Composite 200 Joule Light System

Insole: Anti bacterial and anti Microbial Foam

Sole: PU 2D, oil resistant FO, anti static and HI-CI insulated

Features

>Upper without stitching: No Water Filtration Risk

>Dry Tek Material Resistant to 12 acids and corrosive fluids (standard EN 13832-2)

>Washable up to 60c

>Special Non Slip Crampons for smooth and easy floors, SRC Standard

>Full Black Upper and Black Outsole

>Sizes: **39-46**

Recommended Industries/Use

> Food Industries

> Catering

> Chemical Industries

> Medical

PACKAGING

10 pairs per carton

1 YEAR WARRANTY AGAINST MANUFACTURING DEFECTS



CODE: TCL

70109 TOTAL - FLEX S3

Upper: ON MICRO TD® microfiber, water resistant, Richelieu assembly without lateral stitching

Lining: AIR SYSTEM® black color, up to the toes, slipper feeling

Tongue: Bellows tongue in ON STEAM® microfiber, lined AIR SYSTEM® and padded with 10mm thick foam

Ankle protection: ON STEAM® microfiber, lined AIR SYSTEM® and padded with 10mm thick foam

Toe cap: Ultralight and extra wide 200 joules, Composite LIGHT SYSTEM®

Midsole: Composite FLEX SYSTEM®, anti-magnetic and thermal insulated

Insole: Thermoformed in active carbon dual density foam, antistatic, ESD and antibacterial FRESH TECH®

Sole: PU 2D, TECH SOLE® ankle anti-twist system, oil resistant FO, antistatic, HI-Cl

Sizes: 38 to 46

Suitable for : Inside/Outside

Ideal for : Construction & Public Works / Finishing & Infrastructure / Logistics & Transport, Services / High-Tech & Automotive / Handworkers, Craftsmanship

1 Year Warranty

Made in France



CODE: THB

Honeywell

THE POWER OF CONNECTED

A700 Grey Frame TSR Grey Hard Coat

Feature: Rock solid protection at a rock bottom price Affordably priced and economical for your business Sporty styling

Benefit: It provides a stylish fit for your everyday wearer

Feature: Lightweight design with sport temples and soft temple tip pads moulded universal nose bridge

Benefit: They provide a secure, wrap-around fit and all-day comfort

Feature: 8-base polycarbonate abrasion resistant lenses

Benefit: They provide a 180° field of distortion-free vision



STYLE NO: BEF

North Silicone Full Facepiece Mask 760008A
NIOSH / OSHA / EN-136:1998
CLASS 1

MADE IN MEXICO

Description

The Honeywell North 7600 full face piece features the same craftsmanship and design details that made the 7700 half mask the most popular in the market. It all adds up to a mask with superior fit and reliability

Materials

Facepiece Material > Silicone
Lens > Polycarbonate

Features

- > Silicone mask provides all day comfort
- > **Standard Speech Diaphragm** amplifies workers conversation in noisy work environments
- > Dual flange sealing area provides a wider sealing area with added flexibility for difficult to fit faces
- > Five strap head harness - center straps help to position and hold the mask for a more secure fit even during strenuous jobs requiring lots of movement
- > Nose cup is standard which means less dead air space for increased worker comfort and productivity.
- > Channels exhaled breath meaning lens does not fog up
- > Chin cup positions the facepiece correctly for a more secure fit
- > Lens offers 200° field of vision, for a wider viewing area in all directions plus downward view facilitates going up and down ladders
- > Compatible with Honeywell North range of filters only.
- > Not for use in IDLH (**immediately dangerous to life or health**) environments including atmospheres with less than 19.5% of oxygen.

Applications

Suits various applications requiring respiratory protection against various contaminants including airborne particulates, chemical contamination, gas, vapors and smoke

PACKAGING

1 pc per carton

Honeywell

THE POWER OF **CONNECTED**

CODE: ADH

HW200 ADF Welding Helmet

ANSI Z87.1-2010 - Occupational and Educational Personal Eye and Face Protection Devices

CSA Z94.3 - Eye and Face Protection for industrial processes and hazards



Description

Ideal for more experienced welders, the **HW200 Auto Darkening (ADF)** welding helmet incorporates a high-quality filter with a sleek and lightweight helmet shell, and features solar-powered adjustable **Shade 9-13 ADF** technology for advanced welding applications. The HW200 also features sensitivity and delay adjustments for customizable filter settings. When a welding job requires more than a standard passive filter, ADF helmets provide greater protection, superior comfort and eliminate the need for constant adjustments, allowing for more time spent welding.

Features

- > Grind Mode functionality that ensures the ADF will not darken when used during clean-up work.
- > Sensitivity adjustment that gives the wearer the option to adjust the filter's sensitivity to avoid unwanted darkening from ambient light conditions.
- > An easy ratchet adjustment system for personalized fit and total comfort.
- > Replaceable, padded sweatband.
- > A design that accommodates many safety eyewear and respiratory products.
- > Viewing Area: **7.2" (3.8" x 1.9" / 97mm x 47mm)**
- > Operating temperature range: **-10° C to +55° C (+14° F to +131° F)**

Applications

For welding applications including work above the head

PACKAGING

4 pcs per carton



Honeywell

FIBRE-METAL

CODE: TDN

812614 Honeywell Popweld Nova

FEATURES: IR 10 Lens, Light weight welding shield

USES: Short cycle welding & related applications
such as supervisory & tack welding activities