



LUBENZ

لوبينز

PRODUCT CATALOGUE

"WE CARE ABOUT OUR PLANET SUSTAINIBILITY AND
WE CARE ABOUT OUR PARTNERS STABILITY AND PRODUCTIVITY"



AUTOMOTIVE



COMMERCIAL



MOTORCYCLE



INDUSTRIAL



MARINE



TRANSMISSION



BRAKE FLUIDS



COOLANTS



GEAR OILS



GREASE



TRANSFORMER



SEWING/SPINDLE



ROCK DRILL



CUTTING OIL



About Us

Lubenz is an international lubricant brand that is functioned in types of lubricants such as industrial oils Speciality oils, Marine oils, Agriculture, Machinaries lubricants, Motorcycle lubricants and Automotive lubricants fluids and all types of greases.

We have more than 1000 commercial products including lubricants, special fluids and greases used for passenger vehicles, commercial vehicles, and industrial equipment. One of the notable advantages of our products is that they maintain excellent operational properties in a wide range of temperatures.

We have an extensive network of distributors and strategic partnerships, which help promoting our products in both Local and International Markets. At the global level, our presence is continuously expanding.



RESILIENT SAE 20W-50 API SN

LUBENZ RESILIENT 4T Motor Oils series are enhanced-premium semi-synthetic motor oils meeting the latest industry engine oil specifications. They are designed to provide an excellent level of protection and performance under the most demanding conditions.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS

1L 4L 5L 20L 208L



EXTRA PIXLE SAE 0W-20 API SP

LUBENZ EXTRA PIXLE 0W40 SP is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. LUBENZ EXTRA PIXLE 0W40 SP meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

APPLICATION BENEFITS:

- Excellent thermal and oxidation stability
- Outstanding wear protection
- Reduce oil consumption and effective wear protection
- Engineered to handle the most extreme conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



RESILIENT SAE 10W-40 API SM

LUBENZ RESILIENT 4T Motor Oils series are enhanced-premium semi-synthetic motor oils meeting the latest industry engine oil specifications. They are designed to provide an excellent level of protection and performance under the most demanding conditions.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS

1L 4L 5L 20L 208L



EXTRA PIXLE SAE 5W-30 API SP

LUBENZ EXTRA PIXLE 5W30 SP is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. LUBENZ EXTRA PIXLE 5W30 SP meets and exceeds the requirements of various vehicle manufacturer and industry standard and out performs conventional oils.

APPLICATION BENEFITS:

- Excellent thermal and oxidation stability
- Outstanding wear protection
- Reduce oil consumption and effective wear protection
- Engineered to handle the most extreme conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



RESILIENT SAE 20W-50 API SN

LUBENZ RESILIENT 4T Motor Oils series are enhanced-premium semi-synthetic motor oils meeting the latest industry engine oil specifications. They are designed to provide an excellent level of protection and performance under the most demanding conditions.

APPLICATION BENEFITS:

- Strong protection throughout a long drain interval
- Outstanding thermal and oxidation stability
- Outstanding low temperature properties
- Excellent detergent/dispersant capability

AVAILABLE PACKS

1L 4L 5L 20L 208L



EXTRA PIXLE SAE 10W-30 API GF-5

LUBENZ MOTOBAC 10W30 GF-5 is advanced technology engine oil blended in high performance synthec basestocks forfied with precisely balanced addive system, specifically to help deliver high level of performance and outstanding protecon during long service intervals. It is suitable for the latest downsized engines equipped with stop & start technologies and hybrid engines requiring an API SN specifacon, where very high viscosity index oils are preferred to provide longer oil drain intervals in modern engines.

AVAILABLE PACKS

1L 4L 5L 20L 208L



Premium PEO SAE 40 , API SL/CF

LUBENZ PREMIUM PEO series are monograde crankcase lubricants formulated with high quality base stocks and balanced additive system to provide high level of engine protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise.

Application:

LUBENZ PREMIUM PEO is suitable for use in following:

- Automove gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Suitable for gear and hydraulic applications, if approved.

AVAILABLE PACKS

1L 4L 5L 20L 208L



GLORIA SAE 10W-30 API CH-4

LUBENZ EXTRA PIXLE 0W40 SP is advanced high performance fully synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. LUBENZ EXTRA PIXLE 0W40 SP meets and exceeds the requirements of various vehicle manufacturer and industry standard and outperforms conventional oils.

APPLICATION BENEFITS:

Excellent thermal and oxidation stability
Outstanding wear protection
Reduce oil consumption and effective wear protection
Engineered to handle the most extreme conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



Premium PEO SAE 30 , API SJ/CF

LUBENZ PREMIUM PEO series are monograde crankcase lubricants formulated with high quality base stocks and balanced additive system to provide high level of engine protection and performance. It works harder than other conventional motor oils by continuously preventing dirt and sludge build-up and reduces engine noise.

Application:

LUBENZ PREMIUM PEO is suitable for use in following:

- Automove gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.
- Suitable for gear and hydraulic applications, if approved.

AVAILABLE PACKS

1L 4L 5L 20L 208L



GLORIA SAE 5W-40 , API CI-4/SL

LUBENZ GLORIA CH-4 series is high performance diesel engine oil formulated with highly refined base stocks and advanced technology additives to provide reliable performance in the latest emission designs, including those with EGR systems, as well as satisfying the needs of older engines. It may be used in naturally aspirated and turbocharged diesel and petrol engines, providing excellent protection even under the most strenuous conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



INFINITY SAE 10W-40 , API SJ

LUBENZ INFINITY SJ series is designed with high quality semi-synthetic base stocks and advanced technology additive system to provide very high level of engine protection and performance. It is suitable for higher mileage gasoline fueled automobiles and light duty trucks requiring an API SL specification, where very high viscosity index oils are preferred to provide longer oil drain intervals in modern engines and better oil consumption control in older vehicles where oil usage (burning) is an issue.

Application

LUBENZ INFINITY is suitable for use in following:

- Automove gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.

AVAILABLE PACKS

1L 4L 5L 20L 208L



INFINITY SAE 10W-40 , API SJ

LUBENZ INFINITY SJ series is designed with high quality semi-synthetic base stocks and advanced technology additive system to provide very high level of engine protection and performance. It is suitable for higher mileage gasoline fueled automobiles and light duty trucks requiring an API SL specification, where very high viscosity index oils are preferred to provide longer oil drain intervals in modern engines and better oil consumption control in older vehicles where oil usage (burning) is an issue.

Application

LUBENZ INFINITY is suitable for use in following:

- Automove gasoline and diesel engines.
- Passenger cars, SUVs, light trucks and vans.
- Moderate duty LPG vehicles.

AVAILABLE PACKS

1L 4L 5L 20L 208L



PRO TECH C3 SAE 5W-40 API SN

LUBENZ PRO TECH C3 SN series is a fully synthetic advanced performance engine oils blended in high performance synthetic basestocks fortified with advanced technology additive system, specifically formulated to provide exceptional cleaning power, wear protection and overall performance. It helps prolong the life and maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered automobile engines, with recent multi-valve engines equipped with turbochargers and direct injection fuel systems. Low content in Sulphated Ash, Phosphorus and Sulphur reduces particulate build up in Diesel Particulate Filters (DPF's) and avoids poisoning of Gasoline Catalytic Converters (CAT's)

AVAILABLE PACKS
1L 4L 5L 20L 208L



DIAMOND HDEO 7000 SAE 15W-40 API CG-4

LUBENZ DIAMOND HDEO 7000 15W-40 diesel engine oil is formulated with high quality base stocks and balanced additive system to ensure optimum performance and protection for diesel engines requiring an API CG-4 specification. Suitable for diesel engines fitted on trucks, buses, construction or agricultural machinery for both turbocharged and normally aspirated engines operating under severe service conditions in all seasons.

AVAILABLE PACKS
1L 4L 5L 20L 208L



PRO TECH C2 SAE 5W-30 API SN

LUBENZ PRO TECH C2 SN series is a fully synthetic advanced performance engine oils blended in high performance synthetic basestocks fortified with advanced technology additive system, specifically formulated to provide exceptional cleaning power, wear protection and overall performance. It helps prolong the life and maintain the efficiency of Car Emission Reduction Systems in both diesel and gasoline powered automobile engines, with recent multi-valve engines equipped with turbochargers and direct injection fuel systems. Low content in Sulphated Ash, Phosphorus and Sulphur reduces particulate build up in Diesel Particulate Filters (DPF's) and avoids poisoning of Gasoline Catalytic Converters (CAT's)

AVAILABLE PACKS
1L 4L 5L 20L 208L



DIAMOND HDEO 7000 SAE 10W-40 API CF-4

LUBENZ DIAMOND HDEO 7000 10W-40 diesel engine oil is formulated with high quality base stocks and balanced additive system to ensure optimum performance and protection for diesel engines requiring an API CF-4 specification. Suitable for diesel engines fitted on trucks, buses, construction or agricultural machinery for both turbocharged and normally aspirated engines operating under severe service conditions in all seasons.

AVAILABLE PACKS
1L 4L 5L 20L 208L



GOLD GAS ENGINE OIL SAE 15W-40 GE-JENBACHER

LUBENZ GOLD GAS ENGINE OIL SAE 15W-40 is a heavy-duty lubricant for high performance natural gas engines which require an "ash-less" product. Use of ash-less technology minimizes engine wear, deposits in combustion chambers and exhaust ports and viscosity increase in service.

PERFORMANCE FEATURES AND BENEFITS

- Reliable protection
- Extended oil life
- Ash-less content for two-stroke engines
- Engine efficiency

AVAILABLE PACKS
1L 4L 5L 20L 208L



GOLD GAS ENGINE OIL SAE 20W-50 GE-JENBACHER

LUBENZ GOLD GAS ENGINE OIL SAE 20W-50 is a heavy-duty lubricant for high performance natural gas engines which require an "ash-less" product. Use of ash-less technology minimizes engine wear, deposits in combustion chambers and exhaust ports and viscosity increase in service.

PERFORMANCE FEATURES AND BENEFITS

- Reliable protection
- Extended oil life
- Ash-less content for two-stroke engines
- Engine efficiency

AVAILABLE PACKS
1L 4L 5L 20L 208L



PLATINUM 6000 TRACTOR OIL 10W-30 API GL-4

LUBENZ PLATINUM 6000 TRACTOR OIL series are extra high performance multipurpose tractor lubricants formulated from highly refined base stocks and advanced technology additive system, to meet or exceed transmission and hydraulic fluid requirements. These oils are engineered to deliver the varied lubricant performance properties required in severe duty applications of agricultural and construction equipment drive trains. Moreover it is particularly well suited for reducing wet brake and Power Take-Off (PTO) chattering.

AVAILABLE PACKS
1L 4L 5L 20L 208L



PLATINUM 6000 TRACTOR OIL 15W-40 API CF-4

LUBENZ PLATINUM 6000 TRACTOR OIL series are extra high performance multipurpose tractor lubricants formulated from highly refined base stocks and advanced technology additive system, to meet or exceed transmission and hydraulic fluid requirements. These oils are engineered to deliver the varied lubricant performance properties required in severe duty applications of agricultural and construction equipment drive trains. Moreover it is particularly well suited for reducing wet brake and Power Take-Off (PTO) chattering.

AVAILABLE PACKS
1L 4L 5L 20L 208L



SILVER HDEO 5000 SAE 40 API CF/SF

LUBENZ SILVER HDEO 5000 series are monograde diesel engine oils formulated with high quality base stocks and selected additives to ensure optimum performance and protection for diesel engines requiring an API CF-4/CF-2 specification. Suitable for heavy duty, high output diesel engines where monograde oils are specified. It provides excellent protection in engines, against high temperature piston deposits, wear, corrosion and foaming under severe operating conditions.

AVAILABLE PACKS
1L 4L 5L 20L 208L



SILVER HDEO 5000 SAE 50 API CC/SC

LUBENZ SILVER HDEO 5000 series are monograde diesel engine oils formulated with high quality base stocks and selected additives to ensure optimum performance and protection for diesel engines requiring an API CF-4/CF-2 specification. Suitable for heavy duty, high output diesel engines where monograde oils are specified. It provides excellent protection in engines, against high temperature piston deposits, wear, corrosion and foaming under severe operating conditions.

AVAILABLE PACKS
1L 4L 5L 20L 208L



TOP EDGE 8 SAE 10W-40 API CK-4

LUBENZ TOP EDGE 8 CK-4/SN series are advanced performance low-SAPS fully synthetic diesel engine oils formulated with severely refined base stocks and sophisticated technology additives to provide outstanding engine performance in the latest emission designs, including those with after treatment systems with Diesel Particulate Filters (DPF), Selective Catalytic Reduction (SCR) and Diesel Oxidation Catalyst (DOC). It may be used in both new and old diesel engines for On & Off highway applications, due to its backward compatibility down to CJ-4 specifications and may also be used in gasoline engines requiring the API SN specification.

AVAILABLE PACKS
1L 4L 5L 20L 208L



TOP EDGE 8 SAE 15W-40 API CK-4

LUBENZ TOP EDGE 8 CK-4/SN series are advanced performance low-SAPS fully synthetic diesel engine oils formulated with severely refined base stocks and sophisticated technology additives to provide outstanding engine performance in the latest emission designs, including those with after treatment systems with Diesel Particulate Filters (DPF), Selective Catalytic Reduction (SCR) and Diesel Oxidation Catalyst (DOC). It may be used in both new and old diesel engines for On & Off highway applications, due to its backward compatibility down to CJ-4 specifications and may also be used in gasoline engines requiring the API SN specification.

AVAILABLE PACKS
1L 4L 5L 20L 208L



HYDRAULIC OIL HVI ZF 68 ISO 68

LUBENZ HOXX PLUS HYDRAULIC OIL HVI ZF range of lubricants are high viscosity index Zinc Free Ashless an-wear hydraulic fluids formulated with high quality HVI base stocks and advanced very low ash an-wear additive technology. They are designed to work efficiently in hydraulic & fluid power transmission systems, subjected to wide temperature ranges operang under severe condions. These oils are available in ISO viscosity grades from 15 to 150. Moreover, they are also designed to work in systems where high hydrolyc stability is required, even in presence of high moisture content in hydraulic systems.

AVAILABLE PACKS

1L 4L 5L 20L 208L



HYDRAULIC OIL HVI ZF 46 ISO 46

LUBENZ HOXX PLUS HYDRAULIC OIL HVI ZF range of lubricants are high viscosity index Zinc Free Ashless an-wear hydraulic fluids formulated with high quality HVI base stocks and advanced very low ash an-wear additive technology. They are designed to work efficiently in hydraulic & fluid power transmission systems, subjected to wide temperature ranges operang under severe condions. These oils are available in ISO viscosity grades from 15 to 150. Moreover, they are also designed to work in systems where high hydrolyc stability is required, even in presence of high moisture content in hydraulic systems.

AVAILABLE PACKS

1L 4L 5L 20L 208L



IND COMPRESSOR OIL 32 ISO 32

LUBENZ IND COMPRESSOR OIL of lubricants are supreme performance air compressor oils formulated with high quality base stocks and advanced additive technology, to provide exceptional equipment protection and reliability for compressors operating under mild to severe conditions. They are designed to meet or exceed the requirements of DIN 51506 VD-L standards and demonstrate high resistance to oxidation and deposit formation.

AVAILABLE PACKS

1L 4L 5L 20L 208L



IND COMPRESSOR OIL 46 ISO 46

LUBENZ IND COMPRESSOR OIL of lubricants are supreme performance air compressor oils formulated with high quality base stocks and advanced additive technology, to provide exceptional equipment protection and reliability for compressors operating under mild to severe conditions. They are designed to meet or exceed the requirements of DIN 51506 VD-L standards and demonstrate high resistance to oxidation and deposit formation.

AVAILABLE PACKS

1L 4L 5L 20L 208L



REFRIGERATION OIL ISO 22

LUBENZ LUBETHERM HEAT TRANSFER OIL are high performance HTOs formulated from highly refined base stocks that are resistant to thermal cracking and chemical oxidation & are intended for use in closed indirect heating installations. The flash points of these oils will not decrease significantly in service because of their resistance to thermal cracking at the operating temperatures for which they are recommended.

Meets or exceeds the requirements of: FDA 21 CFR 178.3570, DIN 51522 (1998 - 11), NSF H1, NSF HT1
Classified as ISO 6743-12 Family Q

AVAILABLE PACKS

1L 4L 5L 20L 208L



REFRIGERATION OIL ISO 32

LUBENZ LUBETHERM HEAT TRANSFER OIL are high performance HTOs formulated from highly refined base stocks that are resistant to thermal cracking and chemical oxidation & are intended for use in closed indirect heating installations. The flash points of these oils will not decrease significantly in service because of their resistance to thermal cracking at the operating temperatures for which they are recommended.

Meets or exceeds the requirements of: FDA 21 CFR 178.3570, DIN 51522 (1998 - 11), NSF H1, NSF HT1
Classified as ISO 6743-12 Family Q

AVAILABLE PACKS

1L 4L 5L 20L 208L



LUBETHERM HEAT TRANSFER OIL ISO 32

LUBENZ LUBETHERM HEAT TRANSFER OIL are high performance HTOs formulated from highly refined base stocks that are resistant to thermal cracking and chemical oxidation & are intended for use in closed indirect heating installations. The flash points of these oils will not decrease significantly in service because of their resistance to thermal cracking at the operating temperatures for which they are recommended.

Meets or exceeds the requirements of: FDA 21 CFR 178.3570, DIN 51522 (1998 - 11), NSF H1, NSF HT1
Classified as ISO 6743-12 Family Q

AVAILABLE PACKS
1L 4L 5L 20L 208L



LUBETHERM HEAT TRANSFER OIL ISO 46

LUBENZ LUBETHERM HEAT TRANSFER OIL are high performance HTOs formulated from highly refined base stocks that are resistant to thermal cracking and chemical oxidation & are intended for use in closed indirect heating installations. The flash points of these oils will not decrease significantly in service because of their resistance to thermal cracking at the operating temperatures for which they are recommended.

Meets or exceeds the requirements of: FDA 21 CFR 178.3570, DIN 51522 (1998 - 11), NSF H1, NSF HT1
Classified as ISO 6743-12 Family Q

AVAILABLE PACKS
1L 4L 5L 20L 208L



PILLAR TURBINE OIL ISO 100

LUBENZ PILLAR TURBINE OIL series are supreme performance circulating oils formulated with high quality base stocks and advanced additive technology, to provide exceptional equipment protection and reliability in applications lubricated by circulating systems which are operating under low to medium severity conditions. They are designed to meet or exceed the general requirements of most builders of turbines, vacuum pumps, compressors & bearings and demonstrate high resistance to oxidation and sludge & varnish formation.

AVAILABLE PACKS
1L 4L 5L 20L 208L



PILLAR TURBINE OIL ISO 150

LUBENZ PILLAR TURBINE OIL series are supreme performance circulating oils formulated with high quality base stocks and advanced additive technology, to provide exceptional equipment protection and reliability in applications lubricated by circulating systems which are operating under low to medium severity conditions. They are designed to meet or exceed the general requirements of most builders of turbines, vacuum pumps, compressors & bearings and demonstrate high resistance to oxidation and sludge & varnish formation.

AVAILABLE PACKS
1L 4L 5L 20L 208L



ROXX SPECIAL GEARLUBE ISO 320

LUBENZ ROXX SPECIAL GEARLUBE series of lubricants are supreme performance industrial gear oils, formulated with high quality base stocks fortified with sulfur-phosphorus additive system. They are designed to work efficiently in all types of enclosed gear drives with circulating or splash lubrication systems, where outstanding extreme pressure characteristics (EP/AW properties), extremely high load carrying capability and excellent demulsifying properties are desired. Moreover they offer extremely high protection against micropitting, wear and corrosion in enclosed gears and all types of oil lubricated bearings. Suitable for use in large & small spur bevel, spiral, helical & herringbone gears.

AVAILABLE PACKS
1L 4L 5L 20L 208L



ROXX SPECIAL GEARLUBE ISO 460

LUBENZ ROXX SPECIAL GEARLUBE series of lubricants are supreme performance industrial gear oils, formulated with high quality base stocks fortified with sulfur-phosphorus additive system. They are designed to work efficiently in all types of enclosed gear drives with circulating or splash lubrication systems, where outstanding extreme pressure characteristics (EP/AW properties), extremely high load carrying capability and excellent demulsifying properties are desired. Moreover they offer extremely high protection against micropitting, wear and corrosion in enclosed gears and all types of oil lubricated bearings. Suitable for use in large & small spur bevel, spiral, helical & herringbone gears.

AVAILABLE PACKS
1L 4L 5L 20L 208L



FLUSHING OIL API SP

LUBENZ SP FLUSHING OIL is a solvent free, fast acting, engine cleaning formulation that removes engine deposits, sludge and contaminants with the oil service drain. It contains added zinc for engine wear protection and its fast acting formulation works in 10 minutes. The solvent free formulation protects gaskets and seals from damage during the cleaning process.

PERFORMANCE FEATURES AND BENEFITS

- Ensures optimum oil circulation in the engine
- Safe with DPF's and catalytic converters
- Fast acting, cleans in 10 minutes
- Solvent free to prevent engine seal damage

AVAILABLE PACKS

1L 4L 5L 20L 208L



SEWING MACHINE OIL ISO 15

LUBENZ SP SEWING MACHINE OIL range of lubricants are premium quality oils specifically formulated for the lubrication of high-speed machine elements in industrial sewing machines. These oils are formulated from very high quality hydro-treated, low viscosity base oils and optimum additive technology system to provide improved thermal, oxidation and color stability. They are available in three viscosity grades, LUBENZ SP SEWING MACHINE OIL 10 (ISO VG 10), SM 15 (ISO VG 15) and SM 22 (ISO VG 22).

AVAILABLE PACKS

1L 4L 5L 20L 208L



MONOX MARINE MULTI SYSTEM SAE 40 API CD

LUBENZ MONOX MARINE MULTI SYSTEM series is a range of high performance marine multipurpose system oils formulated with high quality paraffinic base stocks and balanced additive system to ensure optimum performance and excellent protection in low speed, high output cross head marine engines, operating on residual fuels. It has sufficient alkalinity to neutralize any strong acidic combustion products which may enter into the crankcase and it demonstrates high load carrying ability under severe operating conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



MONOX MARINE MULTI SYSTEM SAE 30 API CD

LUBENZ MONOX MARINE MULTI SYSTEM series is a range of high performance marine multipurpose system oils formulated with high quality paraffinic base stocks and balanced additive system to ensure optimum performance and excellent protection in low speed, high output cross head marine engines, operating on residual fuels. It has sufficient alkalinity to neutralize any strong acidic combustion products which may enter into the crankcase and it demonstrates high load carrying ability under severe operating conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



ONYX TRUCK PISTON EO SAE 30 API CF

LUBENZ ONYX TRUCK PISTON EO series is a range of high performance 30 TBN marine diesel engine oils formulated with premium quality base stocks and high performance additive detergent technology to ensure optimum performance and protection for truck piston engines. They are designed to operate efficiently in severe residual-fuelled medium-speed diesel applications found in marine and stationary power industries. These TPEOs provide outstanding residual fuel compatibility and excellent engine cleanliness, especially in crankcase, camshaft areas, ring belt and piston under crowns operating under severe conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



ONYX TRUCK PISTON EO SAE 40 API CF

LUBENZ ONYX TRUCK PISTON EO series is a range of high performance 30 TBN marine diesel engine oils formulated with premium quality base stocks and high performance additive detergent technology to ensure optimum performance and protection for truck piston engines. They are designed to operate efficiently in severe residual-fuelled medium-speed diesel applications found in marine and stationary power industries. These TPEOs provide outstanding residual fuel compatibility and excellent engine cleanliness, especially in crankcase, camshaft areas, ring belt and piston under crowns operating under severe conditions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



VISTA AUTOMATIC TRANSMISSION ATF DEX III

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID TYPE A, DII and DIII are semi synthetic lubricants based on carefully selected highly refined base oils with a very high viscosity index for most automatic transmissions. The improved fluidity at low temperatures ensures optimum performance in all conditions. Its exceptional frictional characteristics provide smooth switching and driving comfort.

- Anti-wear protection: significantly extended transmission life.
- Extended oil life: excellent thermal and oxidation stability
- Increased clutch band and clutch pack capacity.

AVAILABLE PACKS

1L 4L 5L 20L 208L



VISTA AUTOMATIC TRANSMISSION ATF CVT

LUBENZ VISTA AUTOMATIC TRANSMISSION FLUID CVT a high performance continuous variable transmission fluid, formulated with high quality fully synthetic base stocks and advanced additive technology to ensure consistent repeatable, smooth, step-less shifts under a broad range of driving conditions, temperatures and transmissions. It meets or exceeds the requirements of specifications for many Japanese, American & European designed vehicles and is also suitable in most OEMs CVTs with chain and push belt. It provides smoother, consistent all weather step-less shifting, and all-around lubrication protection of the transmission components to help extend transmission service life and provide a smooth driving experience.

AVAILABLE PACKS

1L 4L 5L 20L 208L



ANTIFREEZE COOLANT COOLANT 50%

LUBENZ COOL ANTIFREEZ COOLANT radiator coolant is formulated with high quality corrosion inhibited Mono-Ethylene glycol liquid and carefully selected additives to provide year round automotive cooling system treatment. It is designed to provide complete cooling system protection in a concentration range of 33% to 100% by volume.

Features & Benefits:

- High boiling point delivers better cooling performance in high temperature operating conditions.
- Excellent anti-foam properties.
- Compatible with ordinary summer coolants.

AVAILABLE PACKS

1L 4L 5L 20L 208L



ANTIFREEZE COOLANT COOLANT 100%

LUBENZ COOL ANTIFREEZ COOLANT radiator coolant is formulated with high quality corrosion inhibited Mono-Ethylene glycol liquid and carefully selected additives to provide year round automotive cooling system treatment. It is designed to provide complete cooling system protection in a concentration range of 33% to 100% by volume.

Features & Benefits:

- High boiling point delivers better cooling performance in high temperature operating conditions.
- Excellent anti-foam properties.
- Compatible with ordinary summer coolants.

AVAILABLE PACKS

1L 4L 5L 20L 208L



GEAR OIL ROXX SAE 80W90 API GL-4

LUBENZ GEAR OIL ROXX GL-4 of lubricants are high performance heavy duty gear oils, formulated from high quality base oils and an advanced additive system. These lubricants are designed for automotive heavy-duty transmissions, axles and final drives. Moreover these oils are engineered to work efficiently in transmissions where protection against wear and scoring is required and high level of oil film protection is desired.

AVAILABLE PACKS

1L 4L 5L 20L 208L



GOLDEN TORQUE CONVERTOR HF 32 ISO 32

LUBENZ GOLDEN TORQUE CONVERTOR HF-32 is a high performance dual clutch transmission fluid, formulated with high quality fully synthetic base stocks and advanced additive technology with consistent shear stability for maintaining optimum film thickness for reliable protection of gears and bearings, also providing an outstanding improvement in friction durability enabling longer drain intervals under a broad range of driving conditions, temperatures and transmissions. It is designed specifically to be used as a service-fill DCT transmission fluid for European, Asian and American vehicles equipped with wet & dry dual clutch transmissions.

AVAILABLE PACKS

1L 4L 5L 20L 208L



TRANSFORMER OIL

IEC 60296 BS 148

LUBENZ SOLO TRANSFORMER OIL BS are severely refined hydro-cracked / hydro-treated virgin inhibited insulating oils with highest degree of purity and stability. It is manufactured from judiciously selected blend of latest technology feed stocks, which is highly suitable for all grades of Power & distribution Transformers, Circuit Breakers, Oil filled switches and X-ray equipment.

Features & Benefits

- Very low sulphur and no DBDS.
- Low Pour point.
- High dielectric strength.

AVAILABLE PACKS

1L 4L 5L 20L 208L



TRANSFORMER OIL

IEC 60296 GB 2536-90

LUBENZ SOLO TRANSFORMER OIL BS are severely refined hydro-cracked / hydro-treated virgin inhibited insulating oils with highest degree of purity and stability. It is manufactured from judiciously selected blend of latest technology feed stocks, which is highly suitable for all grades of Power & distribution Transformers, Circuit Breakers, Oil filled switches and X-ray equipment.

Features & Benefits

- Very low sulphur and no DBDS.
- Low Pour point.
- High dielectric strength.

AVAILABLE PACKS

1L 4L 5L 20L 208L



IND SPINDLE OIL

ISO 10

LUBENZ IND SPINDLE OIL are formulated from select high-quality, low viscosity base oils and additives that impart good resistance to oxidation and protection from rust and corrosion. They possess very good resistance to foaming and separate readily from water. Specifically designed for the lubrication of high-speed spindles in machine tools. They are also used in some critical hydraulic, circulation systems and airline oils where the appropriate viscosity grade is selected.

AVAILABLE PACKS

1L 4L 5L 20L 208L



PETRO ROCK DRILL OIL

ISO 68

LUBENZ PETRO ROCK DRILL OIL series of lubricants are supreme performance Pneumatic Rock Drill & Tool oils, formulated with high quality base stocks fortified with sulfur-phosphorus additive system. They are designed to work efficiently in pneumatically operated rock drills in underground and surface mining operations. They offer optimum adhesiveness and emulsification with water to avoid adverse effects of rust and corrosion. Their excellent wear protection property helps in reducing component wear and maintains adequate lubrication film to carry high loads.

AVAILABLE PACKS

1L 4L 5L 20L 208L



PETRO ROCK DRILL OIL

ISO 100

LUBENZ PETRO ROCK DRILL OIL series of lubricants are supreme performance Pneumatic Rock Drill & Tool oils, formulated with high quality base stocks fortified with sulfur-phosphorus additive system. They are designed to work efficiently in pneumatically operated rock drills in underground and surface mining operations. They offer optimum adhesiveness and emulsification with water to avoid adverse effects of rust and corrosion. Their excellent wear protection property helps in reducing component wear and maintains adequate lubrication film to carry high loads.

AVAILABLE PACKS

1L 4L 5L 20L 208L



CUTTING OIL

LUBENZ SP CUTTING OIL is high quality water soluble cutting oil specifically formulated for cutting and grinding operations of metalworking for both ferrous and non-ferrous components. These oils are formulated to provide outstanding emulsion stability & rust inhibition and works satisfactorily for all types of processes involving fine carbon steels.

Features & Benefits

- Outstanding lubricating property.
- Excellent rust and corrosion protection.
- Excellent emulsion stability.
- Excellent cooling of tools and worked components.

AVAILABLE PACKS

1L 4L 5L 20L 208L



SUPER NANO CALCIUM SULPHONATE COMPLEX GREASE

LUBENZ SUPER NANO HIGH TEMP CALCIUM SULPHONATE COMPLEX GREASE, made of the NEW GENERATION calcium sulfonate complex soap designed by LUBENZ. This new soap has enhanced properties in terms of water resistance, load capacity, thermal resistance, anticorrosion properties while keeping a very high level of pumpability and ability to lubricate well in case of high speeds.

AVAILABLE PACKS

250GM 500GM 1KG 2KG 15KG 180KG



PIONEER CALCIUM GREASE MP-2

LUBENZ PIONEER GREASE CALCIUM BASE-EP series are high performance greases, formulated with Calcium based thickeners and an ISO VG 320 mineral base stock to provide added protection against wear, rusting and water washout. They are available in NLGI grades 2 & 3, which are suitable for general purpose automotive applications at moderate temperatures and loads. The suitable operating temperature range is from -20°C to 80°C maximum. It does not contain lead or any other heavy metals which are considered harmful to human health and environment.

AVAILABLE PACKS

250GM 500GM 1KG 2KG 15KG 180KG



ULTIMATE CLAY BASED GREASE HT EP00

LUBENZ ULTIMATE HIGH TEMPERATURE CLAY BASED GREASE are high temperature greases, formulated with bentonite clay based thickener and extreme pressure additive system to provide extra protection against wear, rusting and water washout especially in industrial equipment operating under heavy loads and high temperatures. They are available in NLGI grades ranging from 00 to 3 with base oil viscosity of ISO VG 150 & 320. It retains its consistency at high temperatures and provides good storage stability.

AVAILABLE PACKS

250GM 500GM 1KG 2KG 15KG 180KG



ULTRA NANO CALCIUM SULPHONATE COMPLEX GREASE

LUBENZ ULTRA NANO CALCIUM COMPLEX GREASE are formulated with lithium complex based thickeners, high viscosity index base oils and extreme pressure additive system to provide excellent protection against wear, rusting and water washout. They are available in NLGI grades ranging from 00 to 3 with base oil viscosity of ISO VG 220. They are suitable for most types of Automotive and Industrial applications, including heavy-duty Marine applications where high temperatures, heavy loads and extreme unit pressures are present. EP 1, 2, 3 & 2 Moly greases are suitable for operating temperatures range from -20°C to 140°C, while EP 00 & 0 greases are suitable for operating temperatures ranging from -25°C to 130°C.

AVAILABLE PACKS

250GM 500GM 1KG 2KG 15KG 180KG



XTREME MOLY GREASE LITHIUM EP-3

MOLY BASE GREASE are high performance greases, formulated with lithium based thickeners fortified with Molybdenum Disulfide (MoS₂) solid lubrication, high quality base oils and extreme pressure additive system to provide excellent protection against wear, rusting and water washout. They are available in NLGI grades ranging from 00 to 3 with base oil viscosity of ISO VG 460 & 320. They are suitable for most types of Automotive and Industrial applications, including heavy-duty Marine applications where high temperatures, heavy shock loads and extreme unit pressures are present. MOLY BASE GREASE greases are suitable for operating temperatures range from -20°C to 130°C.

AVAILABLE PACKS

250GM 500GM 1KG 2KG 15KG 180KG



NANO LITHIUM GREASE MP-2

LUBENZ NANO GREASE LITHIUM BASE are high performance greases, formulated with lithium based thickeners and extreme pressure additive system to provide extra protection against wear, rusting and water washout. They are available in NLGI grades ranging from 000 to 3, with base oil viscosities ISO VG 150, 320 and 460. They are suitable for most types of Automotive and Industrial applications, including heavy-duty applications where high unit pressures are present. LUBENZ NANO GREASE LITHIUM BASE are suitable for operating temperatures range from -20°C to 130°C, while LUBENZ NANO GREASE LITHIUM BASE are suitable for operating temperatures range from -25°C to 120°C.

AVAILABLE PACKS

250GM 500GM 1KG 2KG 15KG 180KG



FLUX BRAKE FLUID

DOT-3

LUBENZ FLUX BRAKE FLUID 3 DOT 3 are supreme performance hydraulic brake fluid based on polyethylene glycol ether technology to provide a high level of brake and clutch performance in automove and commercial vehicles. They are designed to meet or exceed the general requirements of most builders of automove disc, drum and an-skid brake systems and clutch systems.

Features & Benefits

- High boiling point
- Minimum swell on rubber components
- Excellent corrosion protecon.

AVAILABLE PACKS

250ML | 500ML | 1LTR | 280LTR



FLUX BRAKE FLUID

DOT-4

LUBENZ FLUX BRAKE FLUID 4 DOT 4 are supreme performance hydraulic brake fluid based on polyethylene glycol ether technology to provide a high level of brake and clutch performance in automove and commercial vehicles. They are designed to meet or exceed the general requirements of most builders of automove disc, drum and an-skid brake systems and clutch systems.

Features & Benefits

- High boiling point
- Minimum swell on rubber components
- Excellent corrosion protecon.

AVAILABLE PACKS

250ML | 500ML | 1LTR | 280LTR



License No: 3463

SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and HENKEL INTERNATIONAL LUBRICANT INDUSTRY LLC may be used through 31-Mar-2024 are as follows:

API SERVICE SYMBOL
Licensee is authorized to display the API Certification Mark on the following products:

BRAND NAME	SAE VISCOSITY GRADE	API SERVICE CATEGORY	CLASSIFICATION
LUBENZ EXTRA PIXLE	0W-16	SP	Resource Conserving, SN PLUS
LUBENZ EXTRA PIXLE	0W-20	SP	Resource Conserving, SN PLUS
LUBENZ EXTRA PIXLE	5W-30	SP	Resource Conserving, SN PLUS
LUBENZ GLORIA	20W-50	CH-4	
LUBENZ GOLRIA	15W-40	CI-4/SL	
LUBENZ INFINITY	10W-30	SL	
LUBENZ INFINITY	10W-40	SN	
LUBENZ INFINITY	20W-50	SL	

Engine Oil Licensing and Certification System
Copyright © 2023, American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark, "Resource Conserving", the API Service Category, and the API Certification Mark "SN PLUS" are either trademarks or registered trademarks of API, 1220 15th St, N.W., Washington, D.C. 20004-3147, U.S.A.

To verify the authenticity of this document, go to: engineoil.api.org/Directory/EOLCSearch

Manager: EOLCS/DEF/MOM
Date: 17-Aug-2023

License No: 3463

SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and HENKEL INTERNATIONAL LUBRICANT INDUSTRY LLC may be used through 31-Mar-2024 are as follows:

API CERTIFICATION MARK
Licensee is authorized to display the API Certification Mark on the following products:

BRAND NAME	SAE VISCOSITY GRADE	ILSAC SPECIFICATION
LUBENZ EXTRA PIXLE	0W-16	GF-6B

Engine Oil Licensing and Certification System
Copyright © 2023, American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark, "Resource Conserving", the API Service Category, and the API Certification Mark "SN PLUS" are either trademarks or registered trademarks of API, 1220 15th St, N.W., Washington, D.C. 20004-3147, U.S.A.

To verify the authenticity of this document, go to: engineoil.api.org/Directory/EOLCSearch

Manager: EOLCS/DEF/MOM
Date: 17-Aug-2023

License No: 3463

SCHEDULE A - LICENSE AGREEMENT

The marks referred to and licensed under the Agreement between API and HENKEL INTERNATIONAL LUBRICANT INDUSTRY LLC may be used through 31-Mar-2024 are as follows:

API CERTIFICATION MARK
Licensee is authorized to display the API Certification Mark on the following products:

BRAND NAME	SAE VISCOSITY GRADE	ILSAC SPECIFICATION
LUBENZ EXTRA PIXLE	0W-20	GF-6A
LUBENZ EXTRA PIXLE	5W-30	GF-6A

Engine Oil Licensing and Certification System
Copyright © 2023, American Petroleum Institute, all rights reserved. API, the API logo, the API Certification Mark, "Resource Conserving", the API Service Category, and the API Certification Mark "SN PLUS" are either trademarks or registered trademarks of API, 1220 15th St, N.W., Washington, D.C. 20004-3147, U.S.A.

To verify the authenticity of this document, go to: engineoil.api.org/Directory/EOLCSearch









Manager: EOLCS/DEF/MOM
Date: 17-Aug-2023



Which?

one are you



 <p>AGRICULTURE OILS</p> <ul style="list-style-type: none"> • AGRI 10W-30 • AGRI 15W-40 • AGRI 10W-40 • AGRI Power Transmission Oil 4 SAE 10 • AGRI Power Transmission Oil 4 SAE 30 • Hydraulic HVLP Series 15, 22, 32, 46 	 <p>INDUSTRIAL</p> <ul style="list-style-type: none"> • Hydraulic Extreme Vibranium series ISO 32, ISO 46, ISO 68, ISO 100, ISO 150, ISO 220. • Heating Oil Extreme Vibranium series 10, 32, 68. • Compressor Oil VDL Series 32, 46, 68, 100, 150, 220, 320 • Hydraulic HLP Series 32, 46, 86, 320, 460 	 <p>GREASES</p> <ul style="list-style-type: none"> • Grease Ca-EP series • Grease Ca-MP series • Grease HT-EP series • Extreme Grease EP series • Extreme Grease MP series • Grease OG Graphite series • Complex Grease • Silicon Base Grease • Sugar Mill Grease 	 <p>AUTOMOTIVE</p> <ul style="list-style-type: none"> • Petrol Engine Oil Series SAE50, SAE60, SAE70, 0W20, 0W30 5W30, 10W40, 15W40, 15W50, 20W40, 20W50, • Diesel Engine oil Series SAE 50, 5W30, 10W30, 10W40, 15W40, 15W50, 20W40, 20W50. • ATF Series ATF DEX II, DEX III, DEX VI, CVTF. • Gear Oil Series SAE-API GL-5, SAE-140 API GL-4
 <p>MARINE</p> <ul style="list-style-type: none"> • Marine Cylinder Oils • Marine Engine Oils • Marine System Oils 	 <p>MOTORCYCLE</p> <ul style="list-style-type: none"> • 4 Stroke SAE20W40 API SN • 4 Stroke SAE 20W50 API SN / JASO MA2 • 2 stroke Engine Oil API TC / JASO 	 <p>SPECIALITY OIL</p> <ul style="list-style-type: none"> • Transformer oil. • Brake fluid DOT 3, DOT 4. • Coolant 40%, 50%, 100%. • Thermic Fluid series. • Rock Drill oil series • Cutting Oils. • Food Grade Grease and lube. 	 <p>HEAVY DUTY</p> <ul style="list-style-type: none"> • Heavy Duty 10W-40 • Heavy Duty 15W-40 • Heavy Duty 20W-50 E7 • Heavy Duty SAE 50 • Heavy Duty SAE 30 • 10W-40 Low SAPS Premium • Heavy Duty Longlife 75W-80

“WE CARE ABOUT OUR PLANET SUSTAINIBILITY AND WE CARE ABOUT OUR PARTNERS STABILITY AND PRODUCTIVITY”



LUBENZ
لوبينز

